

**REST YOUR
ROOFING WORRIES
ON THE EXPERTS**



R O O F S Q U A D



ROOF SQUAD

Roof Squad is an in-house team of DynaRoof comprising of dedicated professionals for the fixing of roofing and cladding products. DynaRoof's journey with its customers does not end with the purchase of roofing sheets. Instead it provides assistance from buying to installation. Thus, it ensures that not only do you get roofing sheets of the highest quality, but also avail expert installation made by knowledgeable and technically sound professionals which guarantees low maintenance. These roof experts are available for inspection, advice, and installation facilities throughout the year.

Advantages of Roof Squad

A professionally trained squad will inspect and install your roof

Only superior quality products will be used to ensure perfect fitting

Get the aesthetic appeal which only our qualified team can give you

Get it customized according to your needs so that your roof is leakage and seepage proof

SCREW SPECIFICATIONS

- **Standard AS 3566** - The AS 3566 is a standard established by the Standard Association of Australia to specify the requirement for a Self Drilling Screw to be suitable for use in Steel and Timber purlins.
- **Grade** - Class 3 Coating is a unique anti-corrosive coating system consisting of 3 distinct layers which combine to give exceptional protection.
- **Base Materials** - Carbon Steel Grade - 1022.
- **Anti-Corrosive Test** - 1000 Hours Salt Spray test done by Regional Testing Centre (Govt. of India) New Delhi and Sriram Institute for Industrial Research - New Delhi.
- Coated with **Xylan** to prevent rusting.
- **PVC Colour caps** are provided to match with the colour of the sheets for an aesthetic look.
- Corrosion proof **SDST(Self Drilling Self Tapping) screws** with **EPDM washers** ensure a strong and weather-tight attachment.
- Tek points of SDST screws act as a drilling bit, with the help of **13RE drilling machine** it gets drilled and tap their own threads into the purlins.



INSTALLATION GUIDELINE

Purlin distance : For Hi Rib Profile sheet

Thickness	Purlin Gap
0.35 & 0.40 mm	0.900 mm to 1.100 mm
0.45 & 0.50 mm	1.100 mm to 1.400 mm
0.55 & 0.60 mm	1.400 mm to 1650 mm
0.80 mm	1650 mm to 1850 mm

Purlin distance : For Tiles Profile sheet

Thickness	Purlin Gap
0.40 mm & 0.50 mm	0.800 mm to 0.950 mm or 1000 mm

Instruction :

- Purlin to be painted with Red Oxide primer coating followed by double coat of plastic enamel paint
- Guard film should be removed before installation



INSTALLATION BY ROOF SQUAD ADVANTAGES

ROOF SQUAD TEAM

- 1) Our installation teams are technically trained and experienced personnel.
- 2) DynaRoof uses imported Xylan coated screws to prevent rusting of purlins and roofing sheets.
- 3) Installation work is undertaken within specified timelines as per customer requirement.
- 4) DynaRoof provides one year service warranty against leakage and seepage.
- 5) Safety norms are maintained (wearing of helmet, harness etc.).
- 6) Site supervision by our senior executives.
- 7) 24 x 7 Helpdesk available.

LOCAL UNSKILLED WORKERS

- 1) Lack the necessary training and experience resulting in higher wastage, increased cost and poor aesthetics.
- 2) Local accessories are used – will cause rusting and damage to purlins and roofing sheets.
- 3) No such procedures are followed - no guidelines adhered.
- 4) No warranty provided against leakage and seepage.
- 5) Safety norms are not adhered to – hazardous working conditions leading to accidents.
- 6) No site supervision – resulting in poor workmanship & delayed timelines.
- 7) No Helpdesk.





FOR WORRY PROOF ROOF
CALL +91 36121 30188





CALL +91-361-2130188



DynaRoof Pvt. Ltd.

Anil Plaza, 5th Floor, G S Road, Guwahati - 781005, India

Phone: 91-361-2465255/256, Fax: 0361-2465257

E-mail: info@dynarroof.com, website: www.dynarroof.com

Factory: 10th Mile, Mawsamai Village, Ri-Bhoi District, Meghalaya - 793101